

# LEDinspect POCKET PRO400

Inspectionlights



**Multi-Angle Flex & Twist**  
High flexibility and diverse adjustment possibilities thanks to multi angle positioning



**400 Lumen**  
Up to 400 lumens and integrated switch for dimming the light



**2 in 1 Function**  
Inspection light & torch light combined in one



**2-year-OSRAM guarantee\***  
Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers

## Product datasheet



### Light is versatile

This high-quality inspection light from OSRAM is designed to illuminate hard-to-reach areas. The POCKET PRO 400 combines a slim design with multi-axis rotation and tilting so that the light can be directed exactly where it is needed. Additionally, the flexible mounting options offer hands-free working. The pocket size with only 6mm depth and the low weight make this inspection light ideal for the workshop. This LED inspection light emits up to 400 lumens. It has a white light with up to 6000K for comfortable working conditions and is therefore designed for wide illumination as well as for the illumination of narrow spaces. The light intensity can be easily adjusted via the on/off switch. In addition, the POCKET PRO 400 has a powerful torch for a concentrated beam of light. It is rechargeable and cordless, with Li-ion battery for constant light output. The lamp has an operating time of up to 3h and a recharging time of approx. 4h. Charging cable and mains plug included. In addition, OSRAM provides a 2-year guarantee on this product\*

# Product datasheet

## Technical data

### Product information

Order reference	LEDIL409
Application (Category and Product specific)	LED inspection lights

### Electrical data

Nominal wattage	9.62 W
Nominal voltage	3.7 V


### Photometrical data

Color temperature	6000 K
Luminous flux	400 lm
Light color LED	White

### LED module information

Number of LEDs per module	2
---------------------------	---

### Dimensions & weight



Product weight	206.00 g
Length	215.0 mm
Width	100.0 mm
Height	55.0 mm

### Colors & materials

Base color	Black / Orange
------------	----------------

### Lifespan

Guarantee	2 years
-----------	---------

## Product datasheet

### Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Scope of battery	Yes
Battery	High-quality lithium-ion battery

### Capabilities

Technology	LED
------------	-----

### Certificates & standards

Standards	CE/EMC/MSDS/ROHS
IK Class	IK06

### Country specific categorizations

Order reference	LEDIL409
-----------------	----------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	04-10-2022
Primary Article Identifier	4052899622906
Declaration No. in SCIP database	In work



Detail



Detail



Detail

### Logistical Data



Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
--------------	---------------------	------------------------------	--------------------------------------	--------	--------------

## Product datasheet

4052899622906	INSPECTION LAMP	Folding carton box 1	100 mm x 55 mm x 190 mm	1.05 dm <sup>3</sup>	248.00 g
4052899624023	INSPECTION LAMP	Shipping carton box 6	224 mm x 189 mm x 232 mm	9.82 dm <sup>3</sup>	1728.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File	
	User instruction LEDinspect POCKET PRO 400
	Movie application LEDinspect Inspection Lights Trailer

#### Application advice:

For more detailed application information and graphics please see product datasheet and user instruction

\*for precise conditions please refer to:

[www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# OSRAM