

## **HenlyBegins™ SEAT BAG**

DH717 [S] (96719)  
DH718 [M] (96720)  
DH719 [L] (96721)  
DH724 [LL] (97980)

### PRODUCT FEATURES

- Expandable capacity
- Large opening for easy put-in and take-out
- Both sides open fastener
- Reinforced frame
- Rain Cover included
- PALS webbing design
- 2 side pockets and 2 drink holder pockets
- Carry Strap included
- Dark gray reflector equipped for night visibility
- Foldable for compact storage

### CAUTION

- \* Read all instructions before use.
- \* Check if all the components are correctly supplied before use.
- \* The bag may fall off due to vibration, so always check for looseness of the straps and always use it appropriately.
- \* Securely fix the mounting straps and buckle.
- \* Install the bag in a stable position that does not interfere with driving. Also, be sure to attach it so that it does not fall off or shift its position.
- \* The maximum load capacity is S (DH-717): 7Kg / M (DH-718): 8Kg / L (DH-719): 10Kg / LL (DH-724): 14Kg.  
If the load exceeds the maximum load weight, it may fall off or be damaged.
- \* If this product is installed for a long period of time, color transfer may occur. Be careful especially in hot places or when it gets wet.
- \* The fabric and sewing of each part may be damaged if handled roughly, such as by applying excessive force.
- \* Although a rain cover is attached, it is not completely waterproof because the bottom surface is not covered.
- \* If the bag or strap comes into contact with a hot part of the vehicle body (engine, muffler, etc.), it may melt and be damaged.  
Check the installation location carefully, and do not fix it in a hot part.
- \* If the mounting strap is scratched or frayed, it may be damaged or fall off, so be sure to replace it before use.

### COMPONENTS

NO.	DESCRIPTION	Q'TY
①	Seat Bag	1
②	Mounting Strap	4
③	Fixing Band ※Size L&LL only	2
④	Carry Strap	1
⑤	Rain Cover	1

### HOW TO INSTALL

- [1]** Fix the mounting straps in 4 places like passenger step, loading hooks or passenger grip etc. using the loop of the strap.  
※ Be sure to fix the mounting straps so that it does not interfere with driving.
- [2]** Attach the seat bag to the mounting straps with buckles, adjust the straps, and fix the bag.  
※ If the bag shifts forward when braking, fix the seat bag also using the carry strap.  
※ Be sure to fix the carry strap so that it does not interfere with driving.

### HOW TO USE THE REINFORCING PLATE ※ Size L&LL only

When the capacity is expanded, the seat bag hangs down. Using the reinforcing plate, it is possible to reduce the hang down. Remove the reinforcing plate fixed to the side with a hook-and-loop fastener. Set the reinforcing plate on the bottom of the bag body and place your luggage on it.



### HOW TO USE FIXING BAND ※ Size L&LL only

Pass the Fixing Band through the tape loop of the flap. Fix the roll mat etc. (maximum load weight 0.5kg), and tie the excess band to prevent fluttering and loosening.



### CARE AND STORAGE

- If the product gets wet, remove dirt and moisture, open the zipper, and dry it in the shade in a well-ventilated place.
- If it gets dirty, wipe it off with a soft cloth dampened with water and a neutral detergent, and dry it in the shade.
- When storing, dry it in the shade, and then store it in a well-ventilated place away from humidity and out of direct sunlight.
- Do not use organic solvents such as thinner, benzine, and parts cleaner.
- Please refrain from washing with water or washing in a washing machine as it may damage the product