

FITTING INSTRUCTIONS FOR CP0208BL CRASH PROTECTORS KAWASAKI Z750 & Z1000 2007





Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away*!

Right-hand side (as you sit on bike)

- Remove the engine bolt arrowed above.
- Take longest stainless engine bar and put nut and washer from kit on end nearest spanner flats until nyloc plastic engages.
- Push bar with nut and washer through bobbin (into counter bore).
- Put shortest black aluminium spacer on bar with reduced diameter away from bobbin.
- Feed this assembly into engine mount as original and tighten until you feel some compression
 from inside the protector. PLEASE NOTE BOBBIN MUST BE POSITIONED AS
 PICTURED ABOVE WITH BIGGER END TOWARD FRONT OF BIKE. Turn a little more
 so that you feel the compression increase slightly. Then apply a quarter turn. Do not overtighten
 as damage can occur to the bike. Do not exceed 40nm of torque.
- Insert bobbin cap as pictured above



Left-hand side (as you sit on bike)

Repeat above procedure using shorter engine bar and longer spacer.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.